

CONCEPTS

Walls & Ceilings Paint- Ultra Matte Finish

CS 169-Interior Use

A high quality emulsion paint with excellent hiding qualities. Provides a uniform Ultra Matte Finish, doesn't show wall imperfections. Used on properly prepared plaster, concrete, bricks, gypsum board. It features durable film, fast drying, ease of application. Spatter resistance formula. Ammonia free.




Performance Features

- Dries to a beautiful, decorative flat finish.
- Spatter-resistant, low odour.
- Easy application and clean up, quick recoat.
- Excellent opacity.

Colors: White and over 3.500 tinted colors are available.

Toxicity: Formulated without lead or mercury

Gloss Level: 0-2 at 60 degree viewing angle.



Performance Guide:

Weather Resistance

No recommended for exterior use.

Heat Resistance

60° C.

Water Resistance

Washable. Allow 7 days after application for firm to cure.

Abrasion Resistance

Good resistance to abrasion.

Solvent Resistance

Good resistance to white spirits. Sensitive to aromatic hydrocarbons and alcohols.



VOC (Volatile Organic Compounds): EU limit value for this product category A/a type WB: Interior matt walls and ceilings (gloss <25@60°), 30 g/l (2010). This product contains max 29 g/l VOC.

Spreading Rate	Volume Solids	Wet Film Thickness	Dry Film Thickness
10 – 11 m ² /L	40%	100 micrometres	40 micrometres
Dry Time at 20°C	Flexibility	Thinning	For Application By
1 hour to touch 2-4 hours to recoat	Passes 6mm mandrel	5% water	Brush, Roller, Spray

Surface Preparation

Surface to be painted must be clean, dry and free of grease, dirt, dust, flaking paint and mildew. Dull glossy areas by sanding. Apply one or two coats of CS 169 Concepts Ultra Matte Finish after priming the surface as outlined below.

New Plaster, Gypsum Board: Prime with a full coat of CS 192 WALL PLUS, Waterborne Micronized Stabilizing Eco Primer or CS 570 THE PERFECT PRIMER Alkyd Multi-primer & sealer.

Masonry, Concrete, Bricks: Prime with CS 181 WALL PLUS, Waterborne – Alkali Resistant Primer or CS 182 WALL PLUS Solventborne, Waterproofing Stabilizing Primer.

Previously Painted Surfaces: If surface is sound, prime with CS 181 WALL PLUS, Waterborne – Alkali Resistant Primer. Fill nail holes and cracks and sand when dry. Patched surfaces should be spot-primed with CS 181 WALL PLUS, Waterborne – Alkali Resistant Primer. If previous coating is old porous lime, apply an overall coat of CS 182 WALL PLUS Solventborne, Waterproofing Stabilizing Primer.

New Wood: Prime surfaces with CS 023 THE PERFECT PRIMER All-Purpose Eco Primer or CS 570 THE PERFECT PRIMER Alkyd Multi Primer & Sealer.

Application

Stir paint thoroughly before use. Apply by brush, roller or spray. Use a short nap roller on smooth surfaces. Thin as 5% with clean water. Do not apply at temperatures below 10°C. Drying times are longer in cool/moist conditions.

Clean Up:

Clean equipment in warm, soapy water after painting. Do not empty into drains or watercourses. Dispose of empty container responsibly and according to local legislation

Precautions Health, Safety and Environmental Protection:

If medical advice is needed, have product container or label at hand• Keep out of reach of children• Do not get in eyes, on skin, or on clothing• Avoid release to the environment•Dispose of contents and container to appropriate waste site or recycled in accordance with local and national regulation•Keep container tightly closed. • Contains 1,2-benzisothiazol-3(2H)-one and reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1). • May produce an allergic reaction. • Call a POISON CENTER, doctor if you feel unwell. • Safety data sheet available on request.

TEL. POISON CENTER GR: 210 7793777

Packaging and Storage

Sizes : 1 litre, 3 litres, 10 litres

Flash Point: none

Storage: not hazardous, no special requirements

