SELECT
Ceiling Paint
Ultra Flat Finish
CS 258

A premium quality full mat acrylic coating, especially formulated for ceilings. Provides a beautiful uniform mat finish, has a long open time and provides maximum diffused light. It features excellent hiding qualities, easy to apply and it is spatter resistance provides a mildew resistant coating for new or previously painted wallboard, acoustic ceiling, cured masonry, plaster and other ceiling substrates.

Performance Features

- Contains mildewcide to control fungi.
- All Acrylic premium quality.
- Tones down ceiling glare and provides maximum diffused light.
- Dries to a beautiful, decorative flat finish.
- Cleans easily, Spatter-resistant.
- Easy application and clean up, quick recoat.
- Excellent opacity.
- Odorless without ammonia and other solvents.

Colors : White and may be tinted to light colors.
Toxicity: Formulated without lead or mercury
Gloss Level: 0-2 at 60 degree viewing angle.



Performance Guide:

Weather Resistance
No recommended for exterior use.

Heat Resistance
60^{O} C.

Water Resistance
Washable. Allow 7 days after application for firm to cure.

Abrasion Resistance
Resists marring, less so in darker colors.

Solvent Resistance
Good resistance to white spirits. Sensitive to aromatic hydrocarbons and alcohols.

VOC (Volatile Organic Compounds): CS 258 SELECT CEILING PAINT Ultra Flat Finish: belongs to the category A/a WB (Interior matt walls and ceilings, gloss<25@60°). This product contains max 11 g/l VOC. EU Limit: 30g/l (2010).

Spreading Rate	Volume Solids	Wet Film Thickness	Dry Film Thickness
10 - 11 m²/L	37%	97 micrometres	36 micrometres

Dry Time at 20°C	Flexibility	Thinning	For Application By
1 hour to touch 2-4 hours to recoat	Passes 6mm mandrel	5% water if necessary	Brush, Roller , Spray

Surface Preparation

Surface to be painted must be clean and free of dirt, grease, flaking paint and mildew. Dull glossy areas by sanding. Apply one or two coats of CS 258 CEILING PAINT after priming the surface as outlined below.
New Plaster, Gypsum Board: Prime with a full coat of CS 192 WALL PLUS Waterborne Micronized Stabilizing Eco Primer or CS 570 THE PERFECT PRIMER Alkyd Multi-primer & sealer.
Masonry, Concrete, Bricks: Prime with CS 192 WALL PLUS Waterborne Micronized Stabilizing Eco Primer or CS 181 WALL PLUS Waterborne, Alkali Resistant Primer.
Previously Painted Surfaces: If surface is sound, prime with CS 023 THE PERFECT PRIMER All-purpose eco Primer. Fill nail holes and cracks and sand when dry. Spot prime patched surfaces with CS 023 THE PERFECT PRIMER All-purpose eco Primer. If previous is old porous lime, apply and overall coat of CS 182 WALL PLUS Solventborne, Waterproofing Stabilizing Primer.
New Wood: Prime surfaces with CS 570 THE PERFECT PRIMER Alkyd Multi-primer & sealer or CS 023 THE PERFECT PRIMER All-purpose eco Primer.

Application

Stir thoroughly before and during use. Apply by brush, roller or spray. Use a short nap roller on smooth surfaces. Thin as 5% with clean water, only if necessary. Do not apply at temperatures below 10^{O}C. Drying times are longer in cool/moist conditions.

Clean Up: Clean equipment in warm, soapy water after painting. Do not empty into drains or watercourses. Dispose of empty container responsibly and according to local legislation.

Precautions Health, Safety and Environmental Protection

•If medical advice is needed, have product container or label at hand. •Keep out of reach of children. •Keep container tightly closed. •Do not get in eyes, on skin, or on clothing. •Avoid release to the environment. •Call a POISON CENTER or a doctor if you feel unwell.•Dispose of contents and container to appropriate waste site or recycled in accordance with local and national regulation. •Safety data sheet available on request.• Contains: mixture of: 5-chloro-2-methyl-4-isothiazolin-3 -one and 2-methyl-2H-isothiazol-3-one (3:1), 1,2-Benzisothiazol-3 (2H) -one, 2-OCTYL-2H-ISOTHIAZOL-3-ONE, 3-Iodo-2-propynyl N-butylcarbamate. May produce an allergic reaction. •Contains a biocidal product with fungicidal & algicidal properties. Active ingredients: butylcarbamate-3-iodo-2-propynyl (55406-53-6), 2-octyl-2H-isothiazol-3-one (26530-20-1) and zinc pyrithione (13463-41-7) to protect the coating (film). Do not empty into drains. The residual water from cleaning of the working equipment must not get into the ground or into surface waters.

POISON CENTER TEL.: +302107793777

Packaging and Storage

Sizes : 1 litre, 5 litres, 10 litres **Flash Point:** none **Storage:** not hazardous, no special requirements

Colorstyle PAINT