

## CHALKBOARD Paint Water Based CS 307

A premium Acrylic based charcoal paint, turns virtually any interior surface into a chalkboard. Available in any deep colors. Turn any space in your home, office into a writing surface. Dries quickly to a decorative finish that is extremely durable. Is formulated to minimize odor and is ammonia free. Soap and water cleanup.




### Performance Features

- Goes in easily and is washable.
- Resists spattering during application.
- Dries to a decorative finish that is extremely durable.
- Is formulated to minimize lingering odors.
- Soap and water clean-up.
- Dries quickly.

**Colors :** Black, available also in any deep color.

**Toxicity:** Formulated without lead, mercury or chromates.

**Gloss Level:** Low Sheen



### Performance Guide:

#### Water Resistance

Washable. Allow 7 days after application for firm to cure.

#### Heat Resistance

Up to 60° C.

#### Abrasion Resistance

Resists marring, less so in darker colors.

#### Solvent Resistance

Good resistance to white spirits. Sensitive to aromatic hydrocarbons and alcohols.



**VOC (Volatile Organic Compounds): CS 307 CHALKBOARD PAINT:** belongs to the category A/I WB (Decorative effect coatings). EU Limit: 200g/l (2010). This product contains maximum 30g/L VOC.

Spreading Rate	Volume Solids	Wet Film Thickness	Dry Film Thickness
11 - 12 m <sup>2</sup> /L	35%	67 micrometres	23 micrometres
Dry Time at 20°C	Flexibility	Thinning	For Application By
1 hour to touch 2-4 hours to recoat	6 mm mandrel	Not applicable	Brush, Roller , Spray

### Surface Preparation

Surface to be painted must be clean and free of dirt, dust, grease and flaking paint. Remove loose material by scraping and sanding. Dull glossy areas by sanding. Apply two coats of CS 307 CHALKBOARD Paint Water Based after priming as outlined below.

**New Wood:** Spot prime all caulked nailholes and patches with CS 023 THE PERFECT PRIMER, All-purpose eco primer. Allow to dry, then apply a full coat of Primer. Sand to a smooth surface.

**New Plaster, Gypsum Board:** Prime with a full coat of CS 192-00 WALL PLUS Waterborne Micronized, Stabilizing Eco primer.

**Ferrous Metal:** Remove rust and loose material before priming exposed metal with CS 568 THE PERFECT PRIMER Alkyd Rust Primer.

**Previously Painted Surfaces:** Prime with CS 023 THE PERFECT PRIMER, All-purpose eco primer.

### Application

Stir thoroughly before use. Apply one or two coats. For best results, use nylon/polyester brush, roller or spray. Thin 5% with clean water. When brushing or rolling, apply generously using short overlapping strokes, always moving from unpainted into painted areas. Do not over apply. Let paint dry before touching up. Do not apply in temperatures below 10°C.

**CAUTION: Because of the additives used in some varieties of colored chalk, which can leave colored "marking" when erased, we recommend using lighter colored chalk designed for use on chalkboard.**

**Clean Up:** Clean brushes and equipment in warm, soapy water immediately after use.

### Precautions Health, Safety and Environmental Protection:

If medical advice is needed, have product container or label at hand • Keep out of reach of children • Do not get in eyes, on skin, or on clothing • Avoid release to the environment • Dispose of contents and container to appropriate waste site or recycled in accordance with local and national regulation • Keep container tightly closed. • Contains 1,2-benzisothiazol-3(2H)-one and reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1). • May produce an allergic reaction. • Call a POISON CENTER, doctor if you feel unwell. • Safety data sheet available on request.

TEL. POISON CENTER GR: 210 7793777

### Packaging and Storage

**Sizes :** 1 litre      **Flash Point:** none      **Storage:** not hazardous, no special requirements

