

SELECT Interior Emulsion Flat Finish CS 515

A superior quality paint that produces a beautiful, uniform, flat finish on properly prepared plaster, concrete, bricks, masonry, gypsum board, and wood. It has no unpleasant odour and features easy application, a spatter-resistant formulation, fast dry, excellent covering qualities and soap and water cleanup. Deep colours in flat paints do not lend themselves to hard usage or washing because they have a tendency to scuff or burnish. For areas subject to excessive wear or rough handling, use CS 519 Select.




Performance Features

- Dries to a beautiful, decorative flat finish.
- Spatter-resistant, low odour.
- Easy application and clean up, quick recoat.
- Excellent opacity.
- Breathable film

Colors : White and over 1.694 tinted colors are available.

Toxicity: Formulated without lead or mercury

Gloss Level: 0-5 at 60 degree viewing angle.



Performance Guide:

Weather Resistance

No recommended for exterior use.

Heat Resistance

60° C.

Water Resistance

Washable. Allow 7 days after application for firm to cure.

Abrasion Resistance

Resists marring, less so in darker colors.

Solvent Resistance

Good resistance to white spirits. Sensitive to aromatic hydro carbons and alcohols.



VOC (Volatile Organic Compounds): EU Limit value for this product category A/a type WB: Interior matt walls and ceilings (gloss <25@60°), 30g/l (2010). This product contains max 29g/l VOC

Spreading Rate

11 - 12 m²/L

Volume Solids

44%

Wet Film Thickness

100 micrometres

Dry Film Thickness

44 micrometres

Dry Time at 20°C

1 hour to touch
2-4 hours to recoat

Flexibility

Passes 6mm mandrel

Thinning

5% water

For Application By

Brush, Roller, Spray

Surface Preparation

Surface to be painted must be clean, dry and free of grease, dirt, dust, flaking paint and mildew. Dull glossy areas by sanding. Apply two coats of CS 515 Select after priming the surface as outlined below.

New Plaster, Gypsum Board: Prime with a full coat of CS 192 Wall Plus Waterborne Micronized Stabilizing Eco Primer or CS 570 The Perfect Primer, Alkyd Multi Primer & Sealer.

Masonry, Concrete, Bricks: Prime with CS 182 Wall Plus Solventborne Waterproofing Stabilizing Primer or CS 181 Wall Plus Waterborne Alkali-Resistant Primer.

Previously Painted Surfaces: If surface is sound, prime with CS 023 The Perfect Primer, All-purpose Eco Primer. Fill nail holes and cracks and sand when dry. Patched surfaces should be spot-primed with CS 023 The Perfect Primer, All-purpose Eco Primer. If previous coating is old porous lime, apply an overall coat of CS 182 Wall Plus Solventborne primer.

New Wood: Prime surfaces with CS 570 The Perfect Primer, Alkyd Multi Primer & Sealer or CS 023 The Perfect Primer, All-purpose Eco Primer.

Application

Stir paint thoroughly before use. Apply by brush, roller or spray. Use a short nap roller on smooth surfaces. Thin as 5% with clean water. Do not apply at temperatures below 10°C. Drying times are longer in cool/moist conditions.

Clean Up: Clean equipment in warm, soapy water.

Precautions Health, Safety and Environmental Protection:

If medical advice is needed, have product container or label at hand • Keep out of reach of children • Do not get in eyes, on skin, or on clothing • Avoid release to the environment • Dispose of contents and container to appropriate waste site or recycled in accordance with local and national regulation • Keep container tightly closed. • Contains 1,2-benzisothiazol-3(2H)-one and reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1). • May produce an allergic reaction. • Call a POISON CENTER, doctor if you feel unwell. • Safety data sheet available on request.

TEL. POISON CENTER GR: 210 7793777

Packaging and Storage

Sizes : 1 litre, 3 litres, 10 litres,

Flash Point: none

Storage: not hazardous, no special requirements

 **Colorstyle** PAINT

