

## SELECT Interior Emulsion Eggshell Finish CS 519

A superior quality paint that dries to an elegant eggshell lustre. Use on properly prepared plaster, concrete, bricks, masonry, gypsum board, and wood. It has no unpleasant odour and features a spatter-resistant formulation, fast dry, and excellent covering qualities. Provides a durable finish that is more washable than a flat paint. Suitable for schools, hospitals, nurseries, offices and areas receiving above normal wear.




### Performance Features

- Dries to an attractive eggshell finish.
- Spatter-resistant, odourless.
- Easy application and clean up, quick recoat.
- Excellent opacity.
- Scrubbable and hard wearing.

**Colors :** White and over 1.694 tinted colors are available.

**Toxicity:** Formulated without lead or mercury

**Gloss Level:** 5 -15 at 60 degree viewing angle.



### Performance Guide:

#### Weather Resistance

No recommended for exterior use.

#### Heat Resistance

Softens above 65°C.

#### Water Resistance

Scrubbable. Allow 7 days after application for firm to cure.

#### Abrasion Resistance

Resists burnishing.

#### Solvent Resistance

Good resistance to white spirits. Sensitive to aromatic hydro carbons and alcohols.



**VOC (Volatile Organic Compounds):** belongs to the category A/a WB [Interior matt walls and ceilings (gloss <25@60°)]. EU Limit: 30g/l (2010). This product contains 29g/L VOC

Spreading Rate	Volume Solids	Wet Film Thickness	Dry Film Thickness
10 - 11 m <sup>2</sup> /L	42%	100 micrometres	42 micrometres
Dry Time at 20°C	Flexibility	Thinning	For Application By
1 hour to touch 2-4 hours to recoat	Passes 6mm mandrel	5% water	Brush, Roller , Spray

### Surface Preparation

Surface to be painted must be clean, dry and free of grease, dirt, dust, flaking paint and mildew. Dull glossy areas by sanding. Apply two coats of CS 519 SELECT Interior Emulsion after priming the surface as outlined below.

**New Plaster, Gypsum Board:** Prime with a full coat of CS 192 WALL PLUS Waterborne Micronized Stabilizing Eco Primer or CS 570 THE PERFECT PRIMER Alkyd Multi-primer & sealer.

**Masonry, Concrete, Bricks:** Prime with CS 182 WALL PLUS Solventborne, Waterproofing Stabilizing Primer or CS 181 WALL PLUS Waterborne Alkali-Resistant Primer.

**Previously Painted Surfaces:** If surface is sound, prime with CS 023 THE PERFECT PRIMER All-purpose Eco Primer. Fill nail holes and cracks and sand when dry. Patched surfaces should be spot-primed with CS 023 THE PERFECT PRIMER All-purpose Eco Primer. If previous coating is old porous lime, apply an overall coat of CS 182 WALL PLUS Solventborne, Waterproofing Stabilizing Primer.

**New Wood:** Prime surfaces with CS 570 THE PERFECT PRIMER Alkyd Multi-primer & sealer or CS 023 THE PERFECT PRIMER All-purpose Eco Primer.

### Application

Stir paint thoroughly before use. Apply by brush, roller or spray. Use a short nap roller on smooth surfaces. Thin as 5% with clean water. Do not apply at temperatures below 10°C. Drying times are longer in cool/moist conditions.

**Clean Up:** Clean equipment in warm, soapy water.

### Precautions Health, Safety and Environmental Protection:

If medical advice is needed, have product container or label at hand• Keep out of reach of children• Do not get in eyes, on skin, or on clothing• Avoid release to the environment•Dispose of contents and container to appropriate waste site or recycled in accordance with local and national regulation•Keep container tightly closed. • Contains 1,2-benzisothiazol-3(2H)-one and reaction mass of 5-chloro-2-methyl-4-isothiazolin-3-one and 2-methyl-2H-isothiazol-3-one (3:1). • May produce an allergic reaction. • Call a POISON CENTER, doctor if you feel unwell. • Safety data sheet available on request.

TEL. POISON CENTER GR: 210 7793777

### Packaging and Storage

**Sizes :** 1 litre, 3 litres, 10 litres

**Flash Point:** none

**Storage:** not hazardous, no special requirements

